

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347  
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961  
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:  
[www.zoeller.com](http://www.zoeller.com)

## DIAPHRAGM PRESSURE TANK DRAWDOWN CHARTS

### Diaphragm Air-E-Tainer® Tanks

Order No.	Model No.	Total Tank Volume Gallons	Drawdown-Gallons			Equiv. Std. Pressure Tank Gallons**	Approx. Size Inches	Ship Wt. Lbs.	NPT	Factory Precharge PSIG
			20/40	30/50	40/60					
10-2367	AT15*	4.5	1.7	1.4	1.2	12	10 x 16	10	3/4"	18
10-2368	AT44	14.0	5.2	4.3	3.8	30	16 x 22	30	1"	28
10-2369	AT66	20.0	7.4	6.2	5.4	42	16 x 29	35	1"	28
10-2370	AT122	33.4	12.3	10.3	9.0	100	16 x 43	52.5	1"	28
10-2371	AT144	44.0	16.3	13.6	11.9	120	21 x 36	66	1-1/4"	38

\* Compact in-line tank

\*\* Air-E-Tainer® tanks will deliver drawdown equivalent to conventional tanks of this size. Air-E-Tainer® tanks 100 PSI maximum working pressure.

CAUTION: Install 10-2347 pressure relief valve on any installation where pump pressure can exceed the maximum working pressure of the tank.



### Diaphragm Tank Stand

10-2372 pump stand for mounting jet pumps on top of 10-2368, 10-2369 and 10-2370 Air-E-Tainer® tanks.



10-2372

## Check and Foot Valves

**Check Valves Spring Controlled** for general service of jet, submersible or centrifugal, for horizontal or vertical application.



### Brass Check Valves

Order Number	NPT
30-0196	1"
30-0197	1-1/4"
30-0198	1-1/2"

**Foot Valves Spring Controlled** for jet or centrifugal pumps. For vertical application.



### Brass Foot Valves

Order Number	NPT
10-2361*	1-1/4"x1"

\*Dual purpose 1" ID 1-1/4" OD threaded.

# Switches and Gauges

## Pressure Switches



**10-2376/10-2377**

Order No.	Switch Setting	Bottom Connection NPT	Maximum Electrical Rating	
			Single Phase	
			115V	230V
10-2376	20-40	1/4 M	1 HP	1-1/2 HP
10-2377	30-50	1/4 M	1-1/2 HP	2 HP
10-2378*	20-40	1/4 F	1 HP	1-1/2 HP

\* Indicates low pressure cut off for low yielding wells.  
NOTE: All switches are two pole.

## Pressure Gauges

Order No.	Max. Pressure	Connection NPT
10-2379	100 PSI	1/4"
10-2380	200 PSI	1/4"



**10-2379  
10-2380**

## Submersible Well Pump Accessories



**10-2345**



**10-2344**



**10-2343 (5 per pkg.)**

Order No.	Description
10-2343	Cable guards
10-2347*	Pressure Relief Valve, 1/2" NPT, 100 PSI max.
10-2345	Submersible Torque Arrestor
10-2344	Wire Splice Kit

\*NOTE: Install a pressure relief valve with any pump capable of producing more than 75 PSI at the tank.



www.zoeller.com

**ZOELLER**  
PUMP CO.

MAIL TO: P.O. BOX 16347  
Louisville, KY 40256-0347  
SHIP TO: 3649 Cane Run Road  
Louisville, KY 40211-1961  
(502) 778-2731 • 1 (800) 928-PUMP  
FAX (502) 774-3624

Manufacturers of . . .

*"QUALITY PUMPS SINCE 1939"*