


Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
<http://www.zoeller.com>

MECHANICAL ALTERNATOR M-PAK

10-0072 — Mechanical Alternator is designed to provide positive mechanical alternation of a duplex (2-pump) system in residential or commercial applications. A float and rod attached to the alternator will operate one pump when a specified water level is reached. As an added feature for peak conditions, both pumping units are automatically placed in operation. Zoeller 10-0075 — Mechanical Alternator is the same as Zoeller 10-0072, with the addition of a high water alarm switch to activate Zoeller 10-0015, Zoeller 10-0016, or Zoeller 10-0126 alarm. The M-Pak is designed for use in a 30" to 36" deep basin. Consult factory for basin depths exceeding 36 inches.

Mechanical Alternator Features:


- Heavy Metal enclosure
- Stainless steel float
- 5 ft. brass rod with adjustable stops
- Gas tight rod seal
- Cover mount stand

ORDER NUMBER	NEMA RATING	VOLTAGE	PHASE
10-0072, 10-0075*	NEMA 1	115V/200-203V/230V	1
10-0076, 10-0077*	NEMA 7&9	115V/200-203V/230V	1
10-0078*	NEMA 4	115V/200-203V/230V	1


* includes dry contact for auxiliary alarm

NEMA 1- General Purpose Indoor Use
NEMA 7&9-Explosion-Proof/ Hazardous Duty Applications
NEMA 4- Watertight/Dust tight for Indoor and Outdoor Use

Consult factory for three phase pump operation.




SINGLE PHASE DUPLEX SYSTEM



SKA366

THREE PHASE DUPLEX SYSTEM



SK1738

Note: All electrical systems must be installed by a qualified licensed electrician according to the National Electrical Code.

SYSTEM SELECTION GUIDE

PUMPS		"M-PAK"		CONTROL PANEL		H.P. RATING FOR SWITCH MECHANISM IN "M-PAK"
No. Req.	Voltage & Phase	Without Alarm Switch	With Alarm Switch	No. Req.	Product No.	
(2)	115V 1Ph Nonautomatic	10-0072 10-0076 *	10-0075 10-0077 * 10-0078	—	—	1 1/2 HP or less
(2)	200-208/230V 1Ph Nonautomatic	10-0072 10-0076 *	10-0075 10-0077 * 10-0078	—	—	2 HP or less
	200-208/230V	10-0072	10-0075 10-0078	(2)	(Consult Factory)	—
(2)	460/575V 3Ph Nonautomatic	10-0072 10-0076 *	10-0075 10-0077 * 10-0078	(2)	(Consult Factory)	—

*Explosion Proof

Additional options — Zoeller Unichack, Alarm Package, Zoeller Fiberglass or Polyethylene Basin.

Standard enclosure is Nema 1, general purpose control. Consult factory for: Weatherproof, raintight, dust-tight Nema ratings.



ZOELLER
PUMP CO.

MAIL TO: P.O. BOX 16347
Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road
Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP
FAX (502) 774-3624

Manufacturers of . .

"QUALITY PUMPS SINCE 1939"