

KT3 Series Pumps

The KT3 uses a double splash protected motor with more starting torque than a standard motor. An innovative cam-action switch/float assembly allows a "drink" nearly twice the standard volume without increasing outside dimensions. An integral, full-flow check valve virtually eliminates blocked pump discharge. The KT3 series pumps now have 3 top inlets adding installation flexibility.



- Three-quart plastic reservoir
- Thermally protected 115 or 230 VAC 3,000 rpm motor with stainless steel shaft
- 18.5 ft maximum lift
- Suitable for gas condensing furnace application
- Inlets: 2 Capped 1-1/8", 1 Open 1-3/8"
- Outlet: Barbed for 3/8" ID tubing
- Factory installed full-flow check valve
- 6 foot power cord and molded plug
- Available with auxiliary safety switch
- Available with 20' of 3/8" vinyl tubing



3 Year Warranty

MODEL	PART NO.	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gal./Hour@ Lift of				Shut off
		VAC	Amps				W	D	H	6'	12'	18'	20'	
KT3		18.5 Foot Head - 3 Qt. Reservoir - Max. Temperature 110°												
KT3-1UL	801217	115	1.7	N	N	5.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3-1ULT	801131	115	1.7	N	Y	6.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3X-1UL	801218	115	1.7	Y	N	5.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3X-1ULT	801132	115	1.7	Y	Y	6.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3-2UL	801219	230	0.8	N	N	5.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3-2ULT	801215	230	0.8	N	Y	6.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3X-2UL	801220	230	0.8	Y	N	5.0	9.25*	5.50	8.5	155	120	50	-	18.5'
KT3X-2ULT	801216	230	0.8	Y	Y	6.0	9.25*	5.50	8.5	155	120	50	-	18.5'


Width at mounting is 11.25"

KT-15 Series Pumps

The KT-15 will provide years of trouble free service. A high impact, corrosion resistant ABS plastic reservoir, combined with a stainless steel motor shaft, makes this pump ideal for gas condensing furnace application.



- Three-quart plastic reservoir
- Thermally protected 115 or 230 VAC 3,000 rpm motor with stainless steel shaft
- 15 ft maximum lift
- Suitable for gas condensing furnace application
- Capped inlet: 1" and 1-3/8" Outlet: Barbed for 3/8" ID tubing
- Full-flow check valve included
- 6 foot power cord and molded plug
- Available with auxiliary safety switch
- Available with 20' of 3/8" vinyl tubing



1 Year Warranty

MODEL	PART NO.	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gal./Hour@ Lift of				Shut off
		VAC	Amps				W	D	H	6'	12'	18'	20'	
KT-15		15 Foot Head - 3 Qt. Reservoir - Max. Temperature 110° F												
KT-15-1UL	801035	115	1.3	N	N	5.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15-1ULT	801037	115	1.3	N	Y	6.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15X-1UL	801036	115	1.3	Y	N	5.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15X-1ULT	801038	115	1.3	Y	Y	6.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15-2UL	801031	230	0.9	N	N	5.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15-2ULT	801033	230	0.9	N	Y	6.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15X-2UL	801032	230	0.9	Y	N	5.0	9.25	5.50	8.25	118	68	-	-	15'
KT-15X-2ULT	801034	230	0.9	Y	Y	6.0	9.25	5.50	8.25	118	68	-	-	15'

Width at mounting is 11.25"