



KL-20 Series Pumps

When a low profile pump is required, the KL-20 is the pump of choice. The KL-20 has a high impact, corrosion resistant, ABS plastic, slim line reservoir with built in check valve.



- ABS plastic slim line reservoir; inlet 1-3/4" high
- Thermally protected 115 or 230 VAC 3,000 rpm motor with 300 series stainless steel shaft
- 2 Inlets (1" & 1-3/8"), height 1-3/4" ideal for gas condensing furnaces or appliances with low condensate drains
- Built-in full flow check valve for barbed 3/8" ID plastic tubing
- 6' power cord with molded plug (nema 5-15p or 6-15p)
- 18 ft maximum lift
- Available with auxiliary safety switch
- Available with 20' of 3/8" vinyl tubing

12 Month Warranty

MODEL	PART NO.	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gal./Hour@ Lift of				Shut off
		VAC	Amps				W	D	H	6'	12'	18'	20'	
KL-20 18 Foot Head – 1Qt. Low Profile Plastic Reservoir – Max. Temperature 110° F										6'	12'	18'	20'	
KL-20-1UL	801054	115	1.7	N	N	5.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20-1ULT	801062	115	1.7	N	Y	6.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20X-1UL	801055	115	1.7	Y	N	5.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20X-1ULT	801063	115	1.7	Y	Y	6.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20-2UL	801056	230	0.9	N	N	5.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20-2ULT	801064	230	0.9	N	Y	6.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20X-2UL	801057	230	0.9	Y	N	5.0	9.25*	5.50	5.25	55	38	-	-	18'
KL-20X-2ULT	801065	230	0.9	Y	Y	6.0	9.25*	5.50	5.25	55	38	-	-	18'

*Width at mounting 11.25".

PAB3 Series Pumps

The PAB is the ideal pump for applications requiring higher lift and greater capacity. The PAB3 has an integral full-flow check valve and a high torque motor.



- Four-quart plastic reservoir
- Thermally protected 115 or 230 VAC 3,000 rpm motor with stainless steel shaft
- 22 maximum lift
- Suitable for gas condensing furnace applications
- Capped inlets: 1-1/8" and 1-3/8", 1" FNPT at base available; Outlet: barbed 3/8" ID tubing
- Factory installed full-flow check valve
- 6 foot power cord and molded plug
- Available with auxiliary safety switch
- Available with 20' of 3/8" vinyl tubing

3 Year Warranty

MODEL	PART NO.	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gal./Hour@ Lift of				Shut off
		VAC	Amps				W	D	H	6'	12'	18'	20'	
PAB3 22 Foot Head - 4 Qt. Reservoir - Max. Temperature 110°										6'	12'	18'	20'	
PAB3-1	801221	115	2.2	N	N	6	9.25*	6.0	9.75	155	135	90	68	22'
PAB3-1T	801225	115	2.2	N	Y	7	9.25*	6.0	9.75	155	135	90	68	22'
PAB3X-1	801222	115	2.2	Y	N	6	9.25*	6.0	9.75	155	135	90	68	22'
PAB3X-1T	801226	115	2.2	Y	Y	7	9.25*	6.0	9.75	155	135	90	68	22'
PAB3-2	801223	230	1.0	N	N	6	9.25*	6.0	9.75	155	135	90	68	22'
PAB3-2T	801227	230	1.0	N	Y	7	9.25*	6.0	9.75	155	135	90	68	22'
PAB3X-2	801224	230	1.0	Y	N	6	9.25*	6.0	9.75	155	135	90	68	22'
PAB3X-2T	801228	230	1.0	Y	Y	7	9.25*	6.0	9.75	155	135	90	68	22'

*Width at mounting 11.25".