

DIMENSIONS AND WEIGHTS

MODEL NO.	FIG.	HP	MOTOR SIZE	DISCH. SIZE	DIMENSIONS IN INCHES					APPROX. SHIP WT.
					A	B	C	D	E	
150S20-1	A	2	4"	3" NPT	27.3	13.6	13.7	3.75	5.2	55
150S50-2	A	5	4"	3" NPT	41.1	23.6	17.5	3.75	5.2	75
150S75-3	A	7 1/2	4"	3" NPT	50.9	29.6	21.3	3.75	5.2	92
150S75-4	A	7 1/2	4"	3" NPT	54.7	29.6	25.1	3.75	5.2	97
150S100-5	A	10	4"	3" NPT	72.8	43.9	28.9	3.75	5.2	151
150S75-4	A	7 1/2	6"	3" NPT	49.9	24.2	25.7	5.38	5.6	135
150S100-5	A	10	6"	3" NPT	54.9	25.4	29.5	5.38	5.6	148
150S150-6	A	15	6"	3" NPT	61.3	28.0	33.3	5.38	5.6	167
150S150-7	A	15	6"	3" NPT	65.0	28.0	37.0	5.38	5.6	169
150S150-8	A	15	6"	3" NPT	68.8	28.0	40.8	5.38	5.6	174
150S200-9	A	20	6"	3" NPT	75.2	30.6	44.6	5.38	5.6	191
150S200-10	A	20	6"	3" NPT	79.0	30.6	48.4	5.38	5.6	193
150S200-11	A	20	6"	3" NPT	82.8	30.6	52.2	5.38	5.6	198
150S250-12	A	25	6"	3" NPT	89.0	33.1	55.9	5.38	5.6	235
150S250-13	A	25	6"	3" NPT	92.8	33.1	59.7	5.38	5.6	238
150S250-14	A	25	6"	3" NPT	96.6	33.1	63.5	5.38	5.6	242
150S300-15	A	30	6"	3" NPT	103.0	35.7	67.3	5.38	5.6	260
150S300-16	A	30	6"	3" NPT	106.8	35.7	71.1	5.38	5.6	262
150S300-17	A	30	6"	3" NPT	110.5	35.7	74.8	5.38	5.6	266
150S400-18	A	40	6"	3" NPT	119.4	40.8	78.6	5.38	5.6	306
150S400-19	A	40	6"	3" NPT	123.2	40.8	82.4	5.38	5.6	308
150S400-20	A	40	6"	3" NPT	127.0	40.8	86.2	5.38	5.6	323
150S400-21	A	40	6"	3" NPT	130.8	40.8	90.0	5.38	5.7	334
150S400-22	A	40	6"	3" NPT	134.5	40.8	93.7	5.38	5.7	338
150S400-23	A	40	6"	3" NPT	138.3	40.8	97.5	5.38	5.7	340
150S500-24	A	50	6"	3" NPT	162.2	57.8	104.4	5.38	6.1	442
150S500-25	A	50	6"	3" NPT	166.0	57.8	108.2	5.38	6.1	444
150S500-26	A	50	6"	3" NPT	169.8	57.8	112.0	5.38	6.1	446
150S500-27	A	50	6"	3" NPT	173.6	57.8	115.8	5.38	6.1	448
150S500-28	A	50	6"	3" NPT	183.4	63.8	119.6	5.38	7.1	450
150S600-29	A	60	6"	3" NPT	193.7	63.8	129.9	5.38	7.1	448
150S600-31	A	60	6"	3" NPT	201.3	63.8	137.5	5.38	7.1	452
150S600-33	A	60	6"	3" NPT	208.8	63.8	145.0	5.38	7.1	456
150S500-24	A	50	8"	3" NPT	143.2	38.8	104.4	7.50	7.5	492
150S500-25	A	50	8"	3" NPT	147.0	38.8	108.2	7.50	7.5	495
150S500-26	A	50	8"	3" NPT	150.8	38.8	112.0	7.50	7.5	497
150S500-27	A	50	8"	3" NPT	154.6	38.8	115.8	7.50	7.5	499
150S500-28	A	50	8"	3" NPT	158.4	38.8	119.6	7.50	7.5	501
150S600-29*	B	60	8"	3" NPT	169.7	41.8	127.9	7.50	7.5	539
150S600-31*	B	60	8"	3" NPT	177.3	41.8	135.5	7.50	7.5	543
150S600-33*	B	60	8"	3" NPT	184.8	41.8	143.0	7.50	7.5	547
150S750-36*	B	75	8"	3" NPT	201.8	47.4	154.4	7.50	7.5	592
150S750-39*	B	75	8"	3" NPT	213.1	47.4	165.7	7.50	7.5	598




Fig. A




Fig. B

NOTES: All models suitable for use in 6" wells, unless otherwise noted.

Weights include pump end with motor in lbs.

* Built into sleeve 3" NPT discharge, 8" min. well dia.

MATERIALS OF CONSTRUCTION

COMPONENT	CYLINDRICAL SHAFT (1-39 Stgs.)
Check Valve Housing	304 Stainless Steel
Check Valve	304 Stainless Steel
Diffuser Chamber	304 Stainless Steel
Split Cone Nut	304 Stainless Steel
Split Cone	304 Stainless Steel
Impeller	304 Stainless Steel
Suction Interconnector	304 Stainless Steel
Inlet Screen	304 Stainless Steel
Seal Ring Support Plate	304 Stainless Steel
Straps	304 Stainless Steel
Cable Guard	304 Stainless Steel
Priming Inducer	304 Stainless Steel
Coupling	316/329 Stainless Steel**
Pump Shaft	431 Stainless Steel
Intermediate Bearings	NBR
Impeller Seal Ring	NBR/PPS
Check Valve Seat	NBR/316 Stainless Steel
Top Bearing	NBR/304 Stainless Steel
Upthrust Disc	Carbon/Graphite
Upthrust Stop Washer	304 Stainless Steel
8" Motor Adaptor Plate	304 Stainless Steel
Sleeve*	316 Stainless Steel
Sleeve Flange	304 Stainless Steel

NOTES: Specifications are subject to change without notice.
***Required for 29-39 stage models.**
**** 4" Coupling made of 316 Stainless Steel.**

