

JPF/JPS/JDF Jet Pumps



GRUNDFOS





Features/Benefits:

- Complete range of shallow and deepwell jetpumps.
- I.E.C. motors for better efficiency, longer life, and quieter operation.
- Corrosion resistant composite components; impeller, ejector and diffuser.
- Rugged Cast Iron (models JPF and JDF) for durability and strength.
- Stainless Steel construction (model JPS) for superior corrosion protection.
- Built in Thermal Overload for motor protection.
- Clean out port (JPF models only) for easy ejector service.

Construction/Operation:

Technical Data:	Series JPF/JDF	Series JPS
Electrical Supply	1x115V or 1x230V	1x115V or 1x230V
Fluid Temperature	95°F JPF (104°F JDF)	95°F
Maximum Working Pressure	87 PSI	87 PSI
Maximum Lift	25 feet JPF, (70 feet JDF)	25 feet
HP Range	1/2, 3/4 & 1 (1/2 & 3/4 JDF) Hp	1/2 & 1 Hp
Suction	1" & 1 1/4" (JPF5 & JDF) NPT	1" NPT
Discharge	1" NPT	1" NPT
Motor	I.E.C.	I.E.C.
Materials:		
Motor Stool	Cast Iron	E-Coated Aluminum
Shaft Seal	Carbon/Ceramic/NBR	Carbon/Ceramic/NBR
O-Rings & Gaskets	NBR	NBR
Pump Housing (Cap)	Cast Iron	Stainless Steel
Impeller	Noryl®	Technopolymer A
Tubing	Polyethylene	Polyethylene
Ejector/Guide Vane	Noryl®	Technopolymer A




 **Grundfos Pumps Corporation** 
 3131 N. Business Park Avenue, Fresno, CA 93727
 (559) 292-8000 FAX (559) 291-1357
Customer Service Centers
 Allentown, PA • Fresno, CA
 (800) 333-1366 FAX (800) 333-1363

 **Grundfos Canada, Inc.**
 2941 Brighton Rd.
 Oakville, ONT L6H 6C9, Canada
 Phone: (905) 829-9533 • FAX (905) 829-9512

 **Bombas Grundfos de Mexico, S.A. de C.V.**
 Boulevard TLC #15, Parque Industrial Stiva Aeropuerto
 C.P. 66600 Apodaca, N.L., Mexico
 Phone: 52-8-144-4000 • FAX 52-8-144-4010

www.us.grundfos.com

Available From:



Technical information listed as a range only and subject to change without notice. Consult a Grundfos product submittal data sheet for exact specifications.

L-JP-SL-001 1/00
 PRINTED IN USA