



SUBMITTAL
B2WF R2

Bell & Gossett

2WF Submersible Sewage Pump



FEATURES

- **Impeller:** Cast iron, semi-open, non-clog, dynamically balanced with pump out vanes for mechanical seal protection.
- **Casing:** Cast iron flanged volute type for maximum efficiency. Designed for easy installation on A10-20 slide rail or base elbow rail systems.
- **Mechanical Seal:** Silicon Carbide vs. Silicon Carbide sealing faces for superior abrasive resistance, stainless steel metal parts, BUNA-N elastomers.
- **Shaft:** Corrosion resistant, 300 series stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.
- **Fasteners:** 300 series stainless steel.
- Capable of running dry without damage to components.
- Designed for continuous operation, when fully submerged.

Bell & Gossett is a brand of ITT
Residential and Commercial Water.

www.bellgossett.com

Engineered for life





ITT

APPLICATIONS

Specifically designed for the following uses:

- Homes
- Sewage systems
- Dewatering/Effluent
- Water transfer
- Light industrial
- Commercial applications

Anywhere waste or drainage must be disposed of quickly, quietly and efficiently.

SPECIFICATIONS

Pump

- Solids handling capabilities: 2" maximum.
- Capacities: up to 185 GPM.
- Total heads: up to 38 feet TDH.
- Discharge size: 2" NPT threaded companion flange as standard. 3" option available but must be ordered separately. (Order no. A1-3)
- Temperature: 104°F (40°C) continuous
140°F (60°C) intermittent.

MOTORS

- Fully submerged in high grade turbine oil for lubrication and efficient heat transfer. All ratings are within the working limits of the motor.
- Class B insulation.

Single phase (60 Hz):

- Capacitor start motors for maximum starting torque.
- Built-in overload with automatic reset.

- SJTOW or STOW severe duty oil and water resistant power cords.
- 1/3 – 1 HP models have NEMA three prong grounding plugs.

Three phase (60 Hz):

- Class 10 overload protection must be provided in separately ordered starter unit.
- STOW power cords all have bare lead cord ends.

■ **Designed for Continuous Operation:** Pump ratings are within the motor manufacturer's recommended working limits, can be operated continuously without damage when fully submerged.

■ **Bearings:** Upper and lower heavy duty ball bearing construction.


■ **Power Cable:** Severe duty rated, oil and water resistant. Epoxy seal on motor end provides secondary moisture barrier in case of outer jacket damage and to prevent oil wicking. Standard cord is 20'. Optional lengths are available.

■ **Motor Cover O-ring:** Assures positive sealing against contaminant and oil leakage.

AGENCY LISTINGS



Tested to UL 778 and CSA 22.2 108 Standards
By Canadian Standards Association — File #LR218526






MOTOR AND MODEL INFORMATION

ORDER NUMBER	HP	PHASE	VOLTS	RPM	IMPELLER DIA. (IN.)	MAX. AMPS	LOCKED ROTOR AMPS	KVA CODE	LOAD MOTOR EFF. %	RESISTANCE		WEIGHT (LBS.)
										START	LINE-LINE	
2WF0311	0.33	1	115	1750	4.69	10.7	30.0	M	54	11.9	1.7	63
2WF0318	0.33	1	208			6.8	19.5	K	51	9.1	4.2	
2WF0312	0.33	1	230			4.9	14.1	L	53	14.5	8.0	
2WF0511	0.5	1	115		5.00	14.5	31.1	J	55	9.3	1.4	65
2WF0518	0.5	1	208			8.0	19.5	K	51	9.1	4.2	
2WF0512	0.5	1	230			7.3	16.5	J	54	11.7	5.6	
2WF0538	0.5	3	200			3.8	12.3	K	75	—	6.7	
2WF0532	0.5	3	230			3.3	9.7	K	75	—	9.9	
2WF0534	0.5	3	460			1.7	4.9	K	75	—	39.4	
2WF0537	0.5	3	575		5.38	1.4	4.3	K	68	—	47.8	85
2WF0718	0.75	1	208			11.0	39.0	K	65	2.6	1.4	
2WF0712	0.75	1	230			9.4	24.8	J	57	4.8	2.3	
2WF0738	0.75	3	200			4.1	21.2	H	74	—	4.3	
2WF0732	0.75	3	230			3.6	17.3	J	76	—	5.6	
2WF0734	0.75	3	460			1.8	8.9	J	76	—	22.4	
2WF0737	0.75	3	575			1.5	7.3	J	71	—	29.2	
2WF1018	1	1	208		5.75	14.0	39.0	K	65	2.6	1.4	85
2WF1012	1	1	230			12.3	30.5	H	60	4.3	1.8	
2WF1038	1	3	200			6.0	21.2	H	74	—	4.3	
2WF1032	1	3	230			5.8	17.3	J	76	—	5.6	
2WF1034	1	3	460			2.9	8.9	J	76	—	22.4	
2WF1037	1	3	575			2.4	7.3	J	71	—	29.2	

DIMENSIONS

(All dimensions are in inches. Do not use for construction purposes.)



Discharge Flange:

- ① 2" NPT standard
- ② 3" NPT optional (order an A1-3)




PERFORMANCE RATINGS (gallons per minute)

Order No.	2WF03	2WF05	2WF07	2WF10
HP ▶	1/3	1/2	3/4	1
RPM ▶	1750	1750	1750	1750
Total Head Feet of Water	10 ▶	80	122	145
	15	36	90	116
	20	—	50	86
	25	—	—	48
	30	—	—	—
	35	—	—	—

COMPONENTS

Item No.	Description
1	Impeller
2	Casing
3	Mechanical Seal
4	Motor Shaft
5	Motor
6	Ball Bearings
7	Power Cable
8	Casing O-Ring



Bell & Gossett

Bell & Gossett and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

2881 East Bayard Street, Seneca Falls NY 13148

Phone 315-568-7123 • Fax 888-322-5877

© 2006 ITT Corporation

Engineered for life