


2 HP GRINDER PUMP SINGLE-SEAL SYSTEMS

THE BEAST



For residential and light commercial applications.

Engineered and assembled simplex grinder package with the 2 HP BEAST grinder pump.

Preassembled / Job-Ready System
Includes:

- 2 HP BEAST Grinder - Model BAGP1-2021
- Guide Rail
- Discharge Piping
- Lifting Chain
- Pull Rod
- Ball Check Valve
- Gate Valve
- Float Switch

Save Time on the Job Site
and Let Us Build-A-BEAST
For You!

www.blueangelpumps.com

2 YEAR
Warranty



2 HP GRINDER PUMP

Single-Seal Preassembled/Job-Ready Systems



63037-BLA1

- 24"x48" Fiberglass Basin
- 230 Volt
- Single Phase
- Shipping Weight, 253 lbs
- 2 Year Warranty



63038-BLA1

- 24"x60" Fiberglass Basin
- 230 Volt
- Single Phase
- Shipping Weight, 268 lbs
- 2 Year Warranty



63039-BLA1

- 24"x72" Fiberglass Basin
- 230 Volt
- Single Phase
- Shipping Weight, 286 lbs
- 2 Year Warranty

PUMP - BAGP1-2021


- **Internal Capacitors - No Control Panel Req'd**
- **Triple Seal Non-Wicking Cord Design**
- **Grit Resistant, Silicon Carbide Seal and For Added Protection Secondary Lip Seal**
- **Stainless Steel Cutler Assembly Effectively Grinds Domestic Sewage Into a Fine Slurry**
- **Heavy Duty Upper and Lower Ball Bearings**
- **Hardened 440c Stainless Steel (56-60 Rockwell C) Shredding Ring and Grinding Impeller - 8300 Cuts Per Second - 1/2 Million Cuts Per Minute**
- **Oil-Filled For Consistant Bearing Lubrication and Maximum Motor Cooling**
- **Single Phase, 230 Volts, 14.5 Amps**
- **Dual Shaft Seal - Full Mechanical Seal (Silicon/Carbide) and Secondary Lip Seal**

ALARM

- **Type 3R water tight enclosure**
- **High water alarm with light**
- **High water float switch**
- **UL Listed for indoor or outdoor applications**
- **Pre-Mounted terminal block for up to 20 amp pump**

BASIN AND RAIL SYSTEM

- **Fiberglass basin with fiberglass anti-floatation devise**
- **Solid fiberglass lid**
- **Stainless steel rail system with brass disconnect**
- **Cast iron ball check valve**
- **Schedule 80 1 1/4" discharge piping out the side wall of basin (24" below cover)**
- **Brass gate valve**
- **Stainless steel lifting chain**
- **4" Inlet Hub and 2" electrical hub supplied loose for field installation**



MOTOR SPECIFICATIONS

MODEL	HP	PHASE	VOLTS	AMPS	Hz
BAGP1-2021	2	1	230	14.5	60

PERFORMANCE GPM

DISCHARGE HEAD	20'	40'	60'	80'	100'
BAGP1-2021	40	40	38	30	10

**ADDITIONAL BUILD-A-BEAST SYSTEMS AVAILABLE
CALL FOR QUOTATION AND SUPPORT!**

BLUE ANGEL™ ENGINEERED PUMPS • 101 Production Drive • Harrison, OH 45030 • 1-888-636-6628

© 2008 Blue Angel Pumps All Rights Reserved