2 HP GRINDER PUMP

Preassembled Drop-In Replacement for Positive Displacement Systems





Designed To Replace Failing Positive Displacement Pump Systems

Engineered and Assembled Grinder System Package with the 2 HP BEAST Dual Impeller Grinder Pump.

Preassembled / Job-Ready Replacement System Includes:

2 HP BEAST Centrifugal Grinder, Dual Impeller Design - Model BAHGP2-2021E1

Stainless Steel Goose Neck

Suspension Plate and Lifting Bolts

Control Float and High Water Alarm Float

Cast Iron Ball Check Valve

Save Time on the Job Site and Let Us Build-A-BEAST For You!

2 HP GRINDER PUMP

Preassembled Drop-In Replacement for Positive Displacement Systems

BARE1-20

- 230 Volt
- Single Phase
- Shipping Weight, 139 lbs
- 2 Year Warranty



PUMP - BAHGP2-2021E1

- Patented High Head, Double Stage Impeller Design
- Doubled Output Pressure, with Unmatched Performance
- PERFORMANCE 150' Shut Off Head Flows to 28 GPM
- Ideal for Long Discharge Runs or High Static Heads
- Heavy Duty Upper and Lower Ball Bearings

CUTTER ASSEMBLY

 Hardened 440C Stainless Steel (56-60 Rockwell C) Shredding Ring and Grinding Impeller - 13,800 Cuts Per Second - 830,000 Cuts Per Minute

IMPFILER

- Two Bronze Castings for Superior Quality and Long Life
- Recessed (Vortex) Design Reduces Bearing Load / Increases Bearing Life and Prevents Clogging

SHAFT SEALS

• Dual Mechanical Seal (Silicon/Carbide)

MOTOR

- Capacitor Start/Run Design for Assured Starting, Strong Torque and Grinding Under Heavy Load
- Utilizes A Low Voltage, Stress-Free Electronic Start Switch
- Pressed Stator for Precise Shaft / Bearing Alignment, Long Life
- Internal Overload Automatic Protection
- Dual Ball Bearings
- Oil-Filled For Consistant Bearing Lubrication and Maximum Motor Cooling

	300																				
	250																				
et	200																				
In Fe																					1
Total Head In Feet	150																				4
ital F																					4
Tc	100																				
	50															F					
	30									DO	TON	OPE	RAT	E AT CUT	HEA -OFF	DS L	OWE	R TF	IAN		4
g	0	Ħ				10					2	0				2					
	10 20 30 40 Capacity Gallons Per Minute									40											

MOTOR SPECIFICATIONS										
MODEL	HP	PHASE	VOLTS	AMPS	Hz					
BARE1-20	2	1	230	16	60					

PERFORMANCE GPM									
DISCHARGE HEAD	50′	100′	150′						
BARE1-20	28	20	0						

ADDITIONAL BUILD-A-BEAST SYSTEMS AVAILABLE CALL FOR QUOTATION AND SUPPORT!

BLUE ANGEL™ ENGINEERED PUMPS • 101 Production Drive • Harrison, OH 45030 • 1-888-636-6628