1/3 HP CAST IRON SUBMERSIBLE SUMP PUMP





• 58 GPM @ 5'

- Durable Cast Iron Volute
- Reliable, Reinforced Poly-Carbonate Impeller
- Stainless Steel Fasteners
- Oil-Filled, Thermally Protected Motor Prevents Overheating
- Top Suction Screen Filters Debris
- High Capacity 1-1/2" NPT Discharge
- Will Replace Most Submersible Sumps Without Any Plumbing Changes

www.blueangelpumps.com

1/3 HP CAST IRON SUBMERSIBLE SUMP PUMP



BCSM33

- Manual Operation
- 20', SJTW Power Cord
- 11" or Wider Sump Basins
- Shipping Weight, 17 lbs
- 3 Year Warranty

NOTE: Use With Single or Double Piggy-Back Float Switch or Control Panel



BCS33

- Vertical Float Switch
- 8', SJTW Power Cord
- 11" or Wider Sump Basins
- ON Level at 9" / OFF Level at 4"
- Shipping Weight, 17 lbs
- 3 Year Warranty




BCST33

- Piggy-Back Tether Float Switch
- 8', SJTW Power Cord
- 14" or Wider Sump Basins
- ON Level at 13" / OFF Level at 7"
- Shipping Weight, 17 lbs
- 3 Year Warranty



BCAP33

- Piggy-Back Cap Switch
- Microprocessor Controlled -No Moving Parts to Wear Out No Adjustment Needed!
- 8', SJTW Power Cord
- 11" or Wider Sump Basins
- Shipping Weight, 17 lbs
- 3 Year Warranty



MOTOR SPECIFICATIONS

VOLTS

120

AMPS

9.5

Hz 60

RPM

1550

95 -	FL					
25						_==
20	\checkmark					
15						
10						ZĂ
						EA
5						
0	46	20	AE	60	76	9
	15	30	45	60	75	

PERFORMANCE							
DISCHARGE HEAD	5′	10'	15'	20'			
Gallons/Minute	58	45	28	2			

FOR PUMP AND SYSTEM ACCESSORIES SEE ACCESSORIES SECTION BLUE ANGEL[™] PUMPS • 101 Production Drive • Harrison, OH 45030 • 1-888-636-6628 © 2008 Blue Angel Pumps All Rights Reserved

MOTOR

Shaded Pole