


Goulds Pumps

3742 DIMENSION PRINT SECTION 1

All Iron, Bronze and Bronze-Fitted Frame-Mounted Centrifugal Pumps

ENGINEERING DATA



GOULDS PUMPS

Goulds Pumps is a brand of ITT Corporation.

www.goulds.com

Engineered for life



WEIGHTS AND DIMENSIONS - DETERMINED BY PUMP

												Dim. "HL" Determined by Pump and Bedplate		
Pump Size	Suction NPT	Discharge NPT	СР	DD Max.	R	W	х	Y	Z	Wt. (lbs.)	56	140	180	
1 x 1¼-5	11/4	1	12¼	31⁄4	¹⁵ /16	2 ¹ / ₂	4 ¹ /8	2 ³ /16	3 ¹ /16	45	4		51/8	
1¼ x 1½-5	11/2	11⁄4	12 ¹ / ₂	33/8	1 ½16	2 ³ / ₄	4	21/4	2 ¹⁵ /16	48	41/4		61/8	

NOTE:

All pumps shipped in vertical discharge position.

May be rotated in 90° increments. Tighten 3/8 -16 casing bolts to 37 ft./lbs. torque.

AVAILABLE MOTOR AND BEDPLATE WEIGHTS AND DIMENSIONS

Motor Frame	HP @ 3500 RPM				C	Wt.	Bedplate Data									
	1 Phase		3 Phase		Max.	Max.	НА	НВ	HD	HE	HF	HG	НР	Wt.		
	ODP	TEFC	ODP	TEFC					ne		•••		•••	(lbs.)		
56	¹ / ₂ or 1 ¹ / ₂	¹ /2 or 1 ¹ /2	1/2 or 1	1/2 or 1	13	45 52 63	8	26	61⁄8	31⁄8	223/8	23⁄8	1	30		
143T			1 ½	1 ½	13¾											
145T	2	2	2 or 3	2	14¼											
182T	3	3		3	165/8		10		71/4	3¾	24	23⁄4	7/8	43		

NOTE: Dimensions and weights vary with manufacturers. Dimensions in inches and weights in lbs.



Goulds Pumps and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

DGL3742 March, 2008 © 2008 ITT Corporation

