



Engineered for life



AC Canned Spherical Motor Centrifugal Pumps

Applications

Specifically designed for the following use:

- Recirc System for Tankless Water Heaters

Specifications

Pump:

- Max Capacities: 6 GPM
- Max Head: 24'
- Pipe Connections:
3/4" Union Connections
- Maximum Working Pressure: 150 PSI
- Maximum Temperature: 230° F
- Rotation: counter clockwise when viewed from the motor end
- Timer and Temperature Controlled

Motor:

- Canned Spherical Type Motor
- 909 - 115 Volt 98 Watts 60 Hz, 3450 RPM
- Automatic Overload Protection
- 959 - 230 Volt 80 Watts 50 Hz, 2850 RPM

Features

Compact Design:

Close coupled, space saving design provides easy installation.

Mounting:

Pump can be mounted horizontally or vertically with motor end down.

Construction:

ASTM bronze construction.

Ceramic Bearing Ball and Carbon Bearing Cap:

High density ceramic bearing ball and graphite impeller bearing cap designed for high efficiency and long life.

Impeller:

Highly efficient and dynamically balanced with carbon bearing for smooth ultra quiet operation.

Casing:

Casing is bronze construction.

Mechanical Seal:

Unique patented design has no mechanical seal which is a potential leak path.

Motor:

Patented spherical motor pump design is ultra quiet and is designed for continuous operation. All ratings are within working limits of the motor.

Noise level:




Whisper quiet, less than 30 db

Weight:

Lightweight construction weighs less than 6lbs.

Materials of Construction (Wetted Parts)

Part	Materials
Pump Housing	ASTM Bronze
"O" Ring	EPDM
Impeller	Nylon/PPO
Bearing	Carbon/Allumina Ceramic
All Other Wetted Parts	316 Stainless Steel or Plastic



ITT
3878 S. Willow, Suite 104
Fresno, CA 93725
Tel: (559) 265-4730 (800) 554-6853
Fax: (559) 265-4740 (800) 453-7523
www.lainginc.com



Engineered for life