

MODEL NO	PART NO	HP	VOLT/PH	Hz	RPM (Nom)	NEMA START CODE	FULL LOAD AMPS	LOCKED ROTOR AMPS	CORD SIZE	CORD TYPE	CORD O.D inch (mm)
3SE1524HD	107922	1.5	230/1	60	1750	B	12.6	23.0	10/3	SOW	0.690 (17.5)
3SE1594HD	107923	1.5	200-230/3	60	1750	H/L	8.8/8.0	30.4/36.0	10/4	SOW	0.750 (19.1)
3SE1544HD	107924	1.5	460/3	60	1750	L	4.0	17.5	10/4	SOW	0.750 (19.1)
3SE2024HD	107926	2.0	230/1	60	1750	B	14.5	29.0	10/3	SOW	0.690 (17.5)
3SE2094HD	107927	2.0	200-230/3	60	1750	J/M	15.4/14.0	44.1/50.8	10/4	SOW	0.750 (19.1)
3SE2044HD	107928	2.0	460/3	60	1750	M	7.0	25.4	10/4	SOW	0.750 (19.1)

IMPORTANT !

- 1.) PUMP MAY BE OPERATED "DRY" FOR EXTENDED PERIODS WITHOUT DAMAGE TO MOTOR AND/OR SEALS.
- 2.) THIS PUMP IS APPROPRIATE FOR THOSE APPLICATIONS SPECIFIED AS CLASS I DIVISION II HAZARDOUS LOCATIONS.
- 3.) THIS PUMP IS NOT APPROPRIATE FOR THOSE APPLICATIONS SPECIFIED AS CLASS I DIVISION I HAZARDOUS LOCATIONS.
- 4.) INSTALLATIONS SUCH AS DECORATIVE FOUNTAINS OR WATER FEATURES PROVIDED FOR VISUAL ENJOYMENT MUST BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE ANSI/NFPA 70 AND/OR THE AUTHORITY HAVING JURISDICTION. THIS PUMP IS NOT INTENDED FOR USE IN SWIMMING POOLS, RECREATIONAL WATER PARKS, OR INSTALLATIONS IN WHICH HUMAN CONTACT WITH PUMPED MEDIA IS A COMMON OCCURRENCE.

Series 3SE-HD


Performance Curve

1.5 & 2.0HP, 1750RPM, 60Hz (Heavy Duty)



www.cranepumps.com

1½", 2" & 3" Discharge



Testing is performed with water, specific gravity 1.0 @ 68° F @ (20°C), other fluids may vary performance

SECTION 1B
PAGE 56
DATE 6/04



A Crane Co. Company

PUMPS & SYSTEMS

USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598