

# SDS1

## Sink Drain System

### FEATURES

- Fully assembled (individually cartoned).
- Capable of running dry without damage to components.
- Severe duty rated oil and water resistant power cable.

### ASSEMBLED COMPONENTS

- EP0411, 0.4 HP, 3/4" solids handling pump is CSA listed.
- CSA listed pump
- A2H11 Vertimaster vertical level switch with 10 foot cord and piggyback plug is UL and CSA listed.
- 10 gallon structural foam basin and cover.
- 1 1/2" NPT threaded vent, discharge and inlet connections.
- 1 1/2" schedule 40 PVC discharge pipe (internal).

### AGENCY LISTINGS



Tested to UL 778 and CSA 22.2 108 Standards  
By Canadian Standards Association  
File #LR38549



### APPLICATIONS

- Laundry tray
- Wet bar sink
- Air conditioning condensate or dehumidifier water
- Residential dishwashers
- Beautician sink

### SPECIFICATIONS

- 0.4 HP, 115 V, 1 PH, 1550 RPM, with 10' cord
- Maximum Amps: 12.
- 3/4" maximum solids handling.
- Capacities: up to 55 GPM.
- Total heads: up to 24 feet.
- Built in overload with automatic reset.

### PERFORMANCE RATINGS

Total Head (feet of water)	GPM
5	53
10	46
15	36
20	21
22.5	10

### DIMENSIONS

(All dimensions are in inches. Do not use for construction purposes.)

