

SDS2

Sink Drain System

FEATURES

- Fully assembled (individually cartoned).
- Capable of running dry without damage to components.
- Severe duty rated oil and water resistant power cable.

ASSEMBLED COMPONENTS

- SP035V, 1/3 HP, 3/8" solids handling pump.
- UL and CSA listed pump.
- 7 gallon polyethylene basin.
- 2" rubber grommet vent
- 1 1/2" threaded inlet and discharge.
- Translucent basin allows easy water level inspection.
- 1 1/2" schedule 40 PVC discharge pipe (internal).



AGENCY LISTINGS



Tested to UL 778 and CSA 22.2 108 Standards
By Canadian Standards Association
File #LR38549



www.goulds.com
Goulds Pumps is a brand of ITT Corporation.

Goulds Pumps is ISO 9001 Registered.

APPLICATIONS

- Laundry tray
- Wet bar sink
- Air conditioning condensate or dehumidifier water
- Residential dishwashers
- Beautician sink

SPECIFICATIONS

- 1/3 HP, 115 V, 1 PH, with 10' cord
- Maximum Amps: 3
- 3/8" maximum solids handling
- Capacities: up to 40 GPM
- Total heads: up to 30 feet
- Built in overload with automatic reset

PERFORMANCE RATINGS

Total Head (feet of water)	GPM
5	40
10	33
15	25
20	17
25	9

DIMENSIONS

(All dimensions are in inches. Do not use for construction purposes.)

