

Models S and SA Sump Pumps Simplex

PUMP GPM SUMP DEPTH MOTOR	DISCH. SIZE TDH NO OF INT. BRGS. FRAME NO.	FEET H.P. R.P.M. VOLTS PH. HTZ.	PUMP No. FOR CERT. BY DATE
------------------------------------	-----------------------------------------------------	------------------------------------------------------	-------------------------------------

MODEL	STANDARD PUMP LENGTHS	
	PUMP LENGTH	NO. INT. BRGS.
SA 2	26"	18"-24"
SA 4	50"	25"-48"
SA 6	74"	49"-72"
SA 8	98"	73"-96"

MODEL S

MODEL SA

WEINMAN

Models SA Sump Pumps Simplex with Square Covers

PUMP GPM SUMP DEPTH COVER SIZE(SQ.) MOTOR R. P. M.	DISCH. SIZE TDH FEET NO. OF INT. BRGS. VAPOR TIGHT YES OR NO FRAME NO. H. P. VOLTS PH. CY.	PUMP NO. FOR CERT. BY DATE
-------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------	-------------------------------------

MOTORS			
1-PHASE	3-PHASE	MOTOR FRAME	C
1750	1750	56C	12
.33	.33	56C	12
.50	.50	56C	12
.75	.75	56C	12

STANDARD SUMP DEPTHS			
SUMP DEPTH	NO INT. BRGS.	SUMP DEPTH	NO INT. BRGS.
0'-2'	0	4'-6'	1
2'-4'	0	6'-8'	1

MODEL	PUMP LENGTH	SUMP DEPTH
SA 2	26	18 -24
SA 4	50	24 -48
SA 6	72	49 -72
SA 8	96	73 -96

SQUARE BASIN COVERS						SQUARE BASIN COVERS & MANHOLE					
B SQ. SUMP	A SQ. COVER	E COVER THICKNESS	COVER DRILLED WHEN SPECIFIED			B SQ. SUMP	A SQ. COVER	E COVER THICKNESS	COVERS DRILLED WHEN SPECIFIED		
			J	K	L				J	K	L
18	20	.31	4	.44	9.50	24	27	.31	4	.63	12.75
24	27	.31	4	.63	12.75	30	34	.31	4	.63	16.25
30	34	.31	4	.63	16.25	36	40	.38	4	.63	19.25
36	40	.38	4	.63	19.25	42	46	.38	8	.63	22.25
42	46	.38	8	.63	22.25	48	52	.50	8	.63	25.25
48	52	.50	8	.63	25.25						

* VENT & COVER DRILLING FOR VAPOR TIGHT CONST. ONLY OR WHEN SPECIFIED
 HIGH WATER ALARM WHEN SPECIFIED

Model SA Sump Pumps Simplex with Round Covers

PUMP GPM SUMP DEPTH COVER SIZE(SQ.) MOTOR R. P. M.	DISCH. SIZE TDH FEET NO. OF INT. BRGS. VAPOR TIGHT YES OR NO FRAME NO. VOLTS PH. CY.	PUMP NO. FOR CERT. BY DATE																																																																																																																						
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="4">MOTORS</th> </tr> <tr> <th>1-PHASE</th> <th>3-PHASE</th> <th>MOTOR FRAME</th> <th>C</th> </tr> <tr> <td>1750</td> <td>1750</td> <td>56C</td> <td>12</td> </tr> <tr> <td>.33</td> <td>.33</td> <td>56C</td> <td>12</td> </tr> <tr> <td>.50</td> <td>.50</td> <td>56C</td> <td>12</td> </tr> <tr> <td>.75</td> <td>.75</td> <td>56C</td> <td>12</td> </tr> </table>			MOTORS				1-PHASE	3-PHASE	MOTOR FRAME	C	1750	1750	56C	12	.33	.33	56C	12	.50	.50	56C	12	.75	.75	56C	12																																																																																														
MOTORS																																																																																																																								
1-PHASE	3-PHASE	MOTOR FRAME	C																																																																																																																					
1750	1750	56C	12																																																																																																																					
.33	.33	56C	12																																																																																																																					
.50	.50	56C	12																																																																																																																					
.75	.75	56C	12																																																																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="4">STANDARD SUMP DEPTHS</th> </tr> <tr> <th>SUMP DEPTH</th> <th>NO INT. BRGS.</th> <th>SUMP DEPTH</th> <th>NO INT. BRGS.</th> </tr> <tr> <td>0'-2'</td> <td>0</td> <td>4'-6'</td> <td>1</td> </tr> <tr> <td>2'-4'</td> <td>0</td> <td>6'-8'</td> <td>1</td> </tr> </table>			STANDARD SUMP DEPTHS				SUMP DEPTH	NO INT. BRGS.	SUMP DEPTH	NO INT. BRGS.	0'-2'	0	4'-6'	1	2'-4'	0	6'-8'	1																																																																																																						
STANDARD SUMP DEPTHS																																																																																																																								
SUMP DEPTH	NO INT. BRGS.	SUMP DEPTH	NO INT. BRGS.																																																																																																																					
0'-2'	0	4'-6'	1																																																																																																																					
2'-4'	0	6'-8'	1																																																																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>MODEL</th> <th>PUMP LENGTH</th> <th>SUMP DEPTH</th> </tr> <tr> <td>SA 2</td> <td>26</td> <td>18 -24</td> </tr> <tr> <td>SA 4</td> <td>50</td> <td>24 -48</td> </tr> <tr> <td>SA 6</td> <td>72</td> <td>49 -72</td> </tr> <tr> <td>SA 8</td> <td>96</td> <td>73 -96</td> </tr> </table>		MODEL	PUMP LENGTH	SUMP DEPTH	SA 2	26	18 -24	SA 4	50	24 -48	SA 6	72	49 -72	SA 8	96	73 -96	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="6">ROUND BASIN COVERS</th> <th colspan="6">ROUND BASIN COVERS & MANHOLE</th> </tr> <tr> <th rowspan="2">B SUMP DIA.</th> <th rowspan="2">A COVER DIA.</th> <th rowspan="2">E COVER THICKNESS</th> <th colspan="3">COVER DRILLING WHEN SPECIFIED</th> <th rowspan="2">B SUMP DIA.</th> <th rowspan="2">A COVER DIA.</th> <th rowspan="2">E COVER THICKNESS</th> <th colspan="3">COVER DRILLING WHEN SPECIFIED</th> </tr> <tr> <th>J</th> <th>K</th> <th>L</th> <th>J</th> <th>K</th> <th>L</th> </tr> <tr> <td>18</td> <td>20</td> <td>.31</td> <td>4</td> <td>.44</td> <td>19</td> <td>24</td> <td>27</td> <td>.31</td> <td>4</td> <td>.63</td> <td>25.50</td> </tr> <tr> <td>24</td> <td>27</td> <td>.31</td> <td>4</td> <td>.63</td> <td>25.50</td> <td>30</td> <td>34</td> <td>.31</td> <td>4</td> <td>.63</td> <td>32.50</td> </tr> <tr> <td>30</td> <td>34</td> <td>.31</td> <td>4</td> <td>.63</td> <td>32.50</td> <td>36</td> <td>40</td> <td>.38</td> <td>4</td> <td>.63</td> <td>38.50</td> </tr> <tr> <td>36</td> <td>40</td> <td>.38</td> <td>4</td> <td>.63</td> <td>38.50</td> <td>42</td> <td>46</td> <td>.38</td> <td>8</td> <td>.63</td> <td>44.50</td> </tr> <tr> <td>42</td> <td>46</td> <td>.38</td> <td>8</td> <td>.63</td> <td>44.50</td> <td>48</td> <td>52</td> <td>.50</td> <td>8</td> <td>.63</td> <td>50.50</td> </tr> <tr> <td>48</td> <td>52</td> <td>.50</td> <td>8</td> <td>.63</td> <td>50.50</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		ROUND BASIN COVERS						ROUND BASIN COVERS & MANHOLE						B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED			B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED			J	K	L	J	K	L	18	20	.31	4	.44	19	24	27	.31	4	.63	25.50	24	27	.31	4	.63	25.50	30	34	.31	4	.63	32.50	30	34	.31	4	.63	32.50	36	40	.38	4	.63	38.50	36	40	.38	4	.63	38.50	42	46	.38	8	.63	44.50	42	46	.38	8	.63	44.50	48	52	.50	8	.63	50.50	48	52	.50	8	.63	50.50						
MODEL	PUMP LENGTH	SUMP DEPTH																																																																																																																						
SA 2	26	18 -24																																																																																																																						
SA 4	50	24 -48																																																																																																																						
SA 6	72	49 -72																																																																																																																						
SA 8	96	73 -96																																																																																																																						
ROUND BASIN COVERS						ROUND BASIN COVERS & MANHOLE																																																																																																																		
B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED			B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED																																																																																																															
			J	K	L				J	K	L																																																																																																													
18	20	.31	4	.44	19	24	27	.31	4	.63	25.50																																																																																																													
24	27	.31	4	.63	25.50	30	34	.31	4	.63	32.50																																																																																																													
30	34	.31	4	.63	32.50	36	40	.38	4	.63	38.50																																																																																																													
36	40	.38	4	.63	38.50	42	46	.38	8	.63	44.50																																																																																																													
42	46	.38	8	.63	44.50	48	52	.50	8	.63	50.50																																																																																																													
48	52	.50	8	.63	50.50																																																																																																																			
<p>* VENT & COVER DRILLING FOR VAPOR TIGHT CONST. ONLY OR WHEN SPECIFIED HIGH WATER ALARM WHEN SPECIFIED</p>																																																																																																																								

Model SA Sump Pumps Duplex with Round Covers

PUMP	DISCH. SIZE	PUMP NO.	
GPM	TDH FEET	FOR	
SUMP DEPTH	NO. OF INT. BRGS.		
COVER SIZE(SQ.)	VAPOR TIGHT YES OR NO		
MOTOR	FRAME NO.	H. P.	
R. P. M.	VOLTS	PH. CY.	CERT. BY
			DATE

MOTORS			
1-PHASE	3-PHASE	MOTOR FRAME	C
1750	1750		
.33	.33	56C	12
.50	.50	56C	12
.75	.75	56C	12

STANDARD SUMP DEPTHS			
SUMP DEPTH	NO INT. BRGS.	SUMP DEPTH	NO INT. BRGS.
0'-2'	0	4'-6'	1
2'-4'	0	6'-8'	1

MODEL	PUMP LENGTH	SUMP DEPTH
SA 2	26	18 - 24
SA 4	50	24 - 48
SA 6	72	49 - 72
SA 8	96	73 - 96

ROUND BASIN COVERS							ROUND BASIN COVERS & MANHOLE						
B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED			B SUMP DIA.	A COVER DIA.	E COVER THICKNESS	COVER DRILLING WHEN SPECIFIED				
			J	K	L				J	K	L		
24	27	.31	4	.63	25.50	30	34	.38	4	.63	32.50		
30	34	.31	4	.63	32.50	36	40	.38	4	.63	38.50		
36	40	.38	4	.63	38.50	42	46	.38	8	.63	44.50		
42	46	.38	8	.63	44.50	48	52	.50	8	.63	50.50		
48	52	.50	8	.63	50.50								

* VENT & COVER DRILLING FOR VAPOR TIGHT CONST. ONLY OR WHEN SPECIFIED
HIGH WATER ALARM WHEN SPECIFIED